

Sewing Pattern — Top 5648

Recommendations on fabric: (natural or mixed) middle/high stretch knit jersey

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

Seam allowance: 1.5 cm for hem/sleeve hems, 1 cm for other seams.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Advice:

Knit fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Back – cut 1
2. Front– cut 1
3. Sleeve – cut 2
4. Collar – cut 1 (Knits have different amounts of stretch so make sure that the sewn collar is wide enough for the head to fit through the opening before sewing it to garment)

INSTRUCTIONS:

1. Sew shoulder seam with a serger or a stretch-stitch. Press toward back.
2. Sew sleeve to armhole matching marks, with serger or stretch-stitch.
3. Sew side and sleeve seam as one with serger or stretch-stitch. Press toward back.
4. Sew the collar into a ring, press seam open. Fold the collar along the center, wrong sides together. Divide the collar into four sections and mark with pins. The seam of the collar should line up with the left front shoulder seam of garment. Divide the neck of the garment into four sections and mark with pins. Match pins and gently stretch collar to fit neck edge between sections as you sew.
5. Serge or finish bottom edges of garment and sleeves. Turn under and topstitch with a stretch-stitch or double needle stitching.

TECHNICAL DRAWING: