

Sewing Pattern — Top 5626

Recommendations on fabric: natural/mixed fabric

You will also need: lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric 1:

1. Upper back part – 2 pieces
2. Lower back part – 2 pieces
3. Upper front part – 2 pieces
4. Lower front part – 2 pieces

Lining:

1. Upper back part – 2 pieces
2. Lower back part – 2 pieces
3. Upper front part – 2 pieces
4. Lower front part – 2 pieces

Our advice: you can use the fabric as the lining.

INSTRUCTIONS:

1. Stitch upper front darts and press them upward.
2. Stitch upper front part to lower front part. Neaten seams and press them upward.
3. Stitch lining front parts.
4. Lay upper back part on the lining right sides together and overstretch along center edge. Overstretch details along upper/lower edges stopping 1 cm before the central seam. Turn the detail right side out and press them. Make decorative stitch along center seam at 1 cm from the edge.
5. Do the same for lower back part.
6. Stitch upper/lower back parts to front part along side seam. Neaten the seams and press them forward.
7. Cut a strap. Fold the strap along the center wrong side out and make a stitch at 0.5 cm from bending. Turn the strap right side out and press it. Sew the strap to front neckline.
8. Fold the strap into right side as well as upper/lower back parts. Lay front part on the lining right sides together and overstretch along three edges: begin at lower front corner, along side seam and along upper edge. Slash the seam, turn details right side out and press them.
9. Fold the rest hole's edges under and press. Make decorative stitch along upper/lower edges stitching unstitched segment at the same time.
10. Pull the strap through back parts as on the sketch.

TECHNICAL DRAWING:

