

## Sewing Pattern — Top 5625

Recommendations on fabric: natural/mixed fabric

You will also need: concealed zip; fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for the hem, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Center front part – 1 piece
4. Side front part – 2 pieces
5. Front facing – 2 pieces
6. Back facing – 2 pieces
7. Front flounce – 1 piece
8. Upper flounce – 1 piece
9. Middle flounce – 1 piece
10. Lower flounce – 1 piece

Fusing:

1. Back facing – 1 piece
2. Front facing – 1 piece

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back facings.

2. Stitch middle back seam, stitch front/back relieves. Neaten seams and press them toward centers.
3. Stitch side seams excluding closure slit into left seam. Neaten right seam and press, neaten left seam and press it apart pressing closure slit.
4. Neaten flounces' upper edge. Turn in flounces' lower/side edges.
5. Mark flounce lines on the top. Stitch upper/middle/lower flounces as marked. Stitch front flounce to front part's upper edge.
6. Stitch front/back facings together along right side seam. Press seams apart. Stitch reinforced facing to top upper edges. Neaten the seam and press it toward the facing. Neaten lower edge with inner facing.
7. Cut a strap. Fold the strap along the center wrong side out and make cm stitch along bending. Turn the strap right side out and press it. Sew the strap to front part.
8. Try the top on, adjust strap's length and sew back end to back part.
9. Stitch the zipper into left side seam.
10. Lay the facings' upper edges right sides together. Fold the facing at 5 mm before zipper's edges and pin to top's upper edge. Fold allowances along the zipper into right side and pin them to upper edge above the lining. Overstitch back part's upper edges. Fold closure allowances into wrong side. Fold inner facing upward and topstitch on seam allowance at 1-2 mm from the seam. Fold the facing into wrong side and fix to zipper braid. Topstitch facing's lower edge along the seam.
11. Neaten the hem, fold it into wrong side and topstitch at 1.5 cm from lower edge.

### **TECHNICAL DRAWING:**

