

Sewing Pattern — Top 5621

Recommendations on fabric: natural/mixed fabric

You will also need: concealed zip; piping.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0 cm for neckline/armholes, 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front part – 2 pieces

INSTRUCTIONS:

1. Stitch back waist darts. Press darts toward back center.
2. Neaten middle back edge. Stitch middle back seam up to closure notch. Press middle seam apart, press closure slits. Stitch the zipper in.
3. Stitch front/back shoulder edges together. Neaten the seams and press them backward.
4. Press the piping along the center and overstitch the neckline/armholes. Overstitch front part up to side seam. Fold piping's ends and sew them to back part by hand.

5. Neaten front seams between notches. Slash the seam at the notch, press it into wrong side and topstitch. Stitch left front part between the notch and side seam. Neaten the seam and press it upward. Pull right front part into this hole and stitch the seam in them same way.
6. Stitch side edges together. Neaten side seams, press them backward.
7. Neaten back hem, fold it into wrong side, press and topstitch.

TECHNICAL DRAWING:

