

## Sewing Pattern — Top 5620

Recommendations on fabric: sheer silk and viscose

You will also need: fusing; piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0 cm for armhole edges, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Right front part – 1 piece
2. Left front part – 1 piece
3. Back part – 2 pieces
4. Side back part – 2 pieces
5. Left waistband – 2 pieces
6. Right waistband – 2 pieces
7. Back facing – 1 piece
8. Front facing – 2 pieces

Fusing: front/back facings.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back facings.
2. Stitch front darts. Slash depths and neaten them.
3. Stitch back relieves. Neaten back relieves and press them toward the center.
4. Stitch shoulder edges together. Neaten seams and press them backward.

5. Press the piping along the center. Overstitch armholes with the piping.
6. Stitch facings along shoulder edges. Neaten the seam and press it frontward. Neaten facings' outer edges.
7. Overstitch front/back necklines with the piping. Turn the seam right side out and press it.
8. Neaten side edges. Stitch side seams and press them apart excluding a hole into right seam. Make decorative stitch along side hole.
9. Overstitch waistbands. Turn the details right side out and press them.
10. Neaten the hem. Press the seam into wrong side.
11. Lay the waistband on front part's right side. Fold neckline facing/the hem toward the waistband. Stitch the waistband to front part with one seam (to right/left front parts correspondingly). Neaten the seam, turn it right side out and press.
12. Topstitch hem allowance. Press the seam.

**TECHNICAL DRAWING:**

