

Sewing Pattern — Blouse 4234

Recommendations on fabric: natural or mixed blouse fabric

You will also need: invisible zipper.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

Seam allowance: on hem of the blouse and hem of sleeve – 2 cm, all other seams – 1 cm

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Fabric:

1. Back - cut 2
2. Front - cut 1 on fold
6. Sleeve – cut 2
7. Collar – cut 1

INSTRUCTIONS:

1. Make pleats along front neckline: center one is a counter pleat; side pleats are directed towards center. Baste pleats with the stitch at 0.5 cm off the edge.
2. Sew darts on back. Press towards center.
3. Sew shoulder and right side seams. Serge and press seam allowances toward back. Serge left side edges separately. Sew seam, leaving an opening for zipper. Sew the zipper into left side seam.
4. Fold collar in half lengthwise and sew short ends, start and finish the stitch exactly near marked line of collar connecting seam. Sew top collar into the neckline. Turn seam allowance of lower collar inside and topstitch into top collar connecting seam.

5. Sew sleeve seam. Serge seam allowance and press toward back. Make a gathering stitch along the sleeve cap for ease. Sew the sleeve into armhole, aligning notches and adjusting ease.
6. Serge bottom edge of garment and sleeve, press under and topstitch.

TECHNICAL DRAWING:

