

Sewing Pattern — Blouse 5607

Recommended fabric: viscose/linen/silk

You will also need: fusible interfacing, 5 buttons.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm for all seams, 2 cm for hem allowance.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Front – cut 2
2. Back – cut 1
3. Front yoke – cut 2
4. Back yoke – cut 1
5. Sleeve – cut 2
6. Cuff – cut 2
7. Front facing – cut 2
8. Back yoke facing – cut 1

Fusible interfacing: front facings, back neck facing, cuffs

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front facings and back yoke facing.
2. Make a gathering stitch at 0.5 cm on front upper edge and gather fullness.
3. Make an inverted pleat on center back and topstitch pleat's inner/outer folds at 0.1 cm distance. Baste along upper edge with a stitch at 0.5 cm from the edge.
4. Sew yokes to fronts and back. Serge and press seam toward yoke.
5. Sew shoulder seams of front facing and back yoke facing and press open. Serge outer edge of facing.
6. Pin front facing to front, right sides together and sew along center front. Sew front facings' lower edges to front along hem marked line. Trim corners. Understitch seam. Turn front facings to inside of garment and press seams.
7. Sew side and shoulder seams, serge and press toward back.
8. Sew front facing/ back yoke facing to neckline. Clip into curves and understitch seam. Turn the facing to the inside of garment and press. Tack facing to shoulder seams.
9. Sew sleeve seam, serge and press. Make a gathering stitch along sleeve lower edge and sleeve cap and gather fullness. The sleeve's lower edge gathers are equal to cuff length. Sew sleeves into armholes, matching marks and adjusting gathers. Serge seam and press.
10. Sew the cuff into a ring, right sides together. Press seam open. Press the cuff along the center. Sew cuff's upper edge to sleeve bottom edge, right sides together. Fold seam allowance of lower edge under, and topstitch along the seam joining the cuff.
11. Serge bottom edge of blouse, fold under and topstitch.
12. Make buttonholes on left front, sew buttons on the right.

TECHNICAL DRAWING:

