

## Sewing Pattern — Dress 5596

Recommendations on fabric: sheer natural/mixed fabric;  
chiffon (for train)

You will also need: concealed zip; stiff braid of 0.75 cm width;  
clue web

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for hem

**Attention!** First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Center front part – 1 piece
4. Side front part – 2 pieces

#### Chiffon:

1. Train – 2 pieces

#### Lining:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Center front part – 1 piece
4. Side front part – 2 pieces

You can use the fabric as lining. The lining ends at back slit's top.

### **INSTRUCTIONS:**

1. Stitch middle back seam to slit notch. Stitch front/back relieves into fabric details. Neaten middle back seam and press it apart pressing the slit. Neaten other seams and press them toward the center.

2. Stitch side seams excluding closure segment into left seam. Neaten seam allowances and press them apart. Stitch the zipperin.
3. Cut the braid into 6 pieces. Stitch pieces to allowances of right seam, relieve seams and middle back seam between waistline and dress upper edge.
4. Stitch middle back seam, front/back relieves, side seams into lining details excluding closure slit. Neaten seams andpress them.
5. Lay the dress on the lining right sides together. 5 mm before the zipper: fold the lining out and pin it to dress's upper edge. Fold closure allowances into right side and pin them to upper edge (over the facing). Stitch upper edges together. Fold closure allowances into wrong side. Fold the lining upwards and topstitch on the seam allowance at 1-2 mm from the seam. Fold the lining into wrong side and fix it to zipper braid.
6. Neaten dress/lining hems, fold them into wrong side and topstitch on wrong side.
7. Stitch trains together, neaten them and press. Fold edges into wrong side and sew.
8. Make a hole into the dress. Pull the train into the hole, tie train's ends to fit it.

**TECHNICAL DRAWING:**

