

## Sewing Pattern — Dress 5584

Recommendations on fabric: natural/mixing fabric

You will also need: concealed zip; fusing; piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0 cm along upper front/back part's outer edges, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Upper back part – 2 pieces
2. Back yoke – 2 pieces
3. Upper front part – 2 pieces
4. Front yoke – 2 pieces
5. Skirt – 1 piece

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of one front/back yoke.
2. Stitch shoulder edges of corresponding front/back parts. Neaten seams and press them backward.
3. Overstitch back/front inner (straight) edge with the piping. Leave the edge joining side/shoulder seams raw.
4. Make loose stitch at 0.5 cm from lower edges of upper front/back seams. Make gathering between the notch and side seam.
5. Lay front yokes right sides together. Insert upper front parts between them coinciding notches so

that front part's right side was on doubled yoke's right side. Stitch details with the same seam. Neaten the seam, turn it right side out and press. Stitch the yoke to upper back part in the same way. Work with the yoke as with one piece.

6. Stitch right side seam, neaten it and press apart.

7. Make one-side pleats into skirt.

8. Lay yoke's lower edge on the skirt. Stitch the seam, neaten it and press it upwards. Make decorative stitch at 1 mm from the seam.

9. Stitch left side seam excluding closure slit. Neaten seams and press them apart pressing closure slit. Stitch the zipper in.

10. Overstitch front/back open edges with the piping. Fix piping's ends by hand. Press seams.

11. Neaten dress hem, fold it into wrong side and topstitch at 0.5 cm from lower edge.

#### **TECHNICAL DRAWING:**

