

Sewing Pattern — Dress 5582

Recommendations on fabric: natural/mixed fabric.

You will also need: concealed zip; decorative band for a strap, piping

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 0 cm for armholes, 2.5 cm for upper back/front part's upper edge, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Upper back part – 1 piece
2. Lower back part – 1 piece
3. Back yoke – 2 pieces
4. Upper front part – 1 piece
5. Lower front part – 1 piece
6. Front yoke – 2 pieces

INSTRUCTIONS:

1. Apply the fusing to wrong side of one back/front yoke.
2. Make loose stitch at 0.5 cm from skirt's upper edge/upper front/back part's lower edge. Make pleats.
3. Lay front yokes right sides together. Insert upper front part so that front part laid on doubled yoke right sides together. Stitch three details with one seam. Neaten the seam, turn it right side out, then press. Do the same for back yoke and back part.
4. Lay front yoke/lower front part's lower edges together. Stitch together, neaten the seam and press it upward. Make decorative topstitching at 1 mm from the seam. Do the same for the yoke and lower back part.

5. Stitch side seams leaving a segment into left seam unstitched (zipper place). Neaten seams and press them apart, pressing closure slits. Stitch the zipper in.
6. Press the piping along the center and overstretch armhole edges with it.
7. Fold piping's ends under and fix them by hand.
8. Neaten upper front/back parts' upper, fold it under first by 0.5 cm, then by 2 cm, then topstitch.
9. Pull decorative band into the dress making straps of necessary length.
10. Neaten dress hem, fold it under and topstitch at 0.5 cm from lower edge.

TECHNICAL DRAWING:

