

Sewing Pattern — Blouse 5571

Recommendations on fabric: silk/viscose

You will also need: fusing; piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 0 cm for garment/sleeve hems, waistband, shaped ties and front bands allowances

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Right front part – 1 piece
2. Left front part – 1 piece
3. Back part – 2 pieces
4. Side back part – 2 pieces
5. Collar – 2 pieces
6. Waistband – 2 pieces
7. Back sleeve – 2 pieces
8. Front sleeve – 2 pieces

Fusing: outer collar.

INSTRUCTIONS:

1. Apply the fusing to wrong side of outer collar.
2. Stitch front darts. Slash darts' depths and neaten them.
3. Stitch back relieves. Neaten them and press toward back center.
4. Neaten blouse's side edges. Stitch side seams and press them apart leaving a hole in left seam. Topstitch the hole in left seam. Stitch shoulder seams, neaten them and press backwards.

5. Lay collars together. Overstitch inner collar with outer collar, cut corner allowances and turn the collar right side out. Press the collar.
6. Stitch the waistband to right/left front part. Neaten the seam.
7. Press the piping along the center. Overstitch edges of front neckline, waistband, front/back parts' hems, back sleeves' hems, sleeve shaped tie, front sleeves' hems and shaped tie with piping.
8. Stitch sleeve seams and neaten them. Press sleeve seams.
9. Stitch outer collar into neckline, fold inner collar's open edge under and topstitch it along joining seam.
10. Stitch sleeves easing them along sleeve caps. Neaten joining seams.

TECHNICAL DRAWING:

