

Sewing Pattern — Skirt 5570

Recommendations on fabric: nature/mixed fabric

You will also need: fusing; zipper; decorative cord.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams, 3 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center front skirt – 1 piece
2. Side front skirt – 2 pieces
3. Small sacking – 2 pieces
4. Large sacking – 2 pieces
5. Front yoke – 1 piece
6. Front facing – 1 piece
7. Center back skirt – 1 piece
8. Side back skirt – 2 pieces
9. Back yoke – 1 piece
10. Back facing – 1 piece

Fusing: front/back facing.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front/back facing.
2. Lay small sacking on side front skirt right sides together. Overstitch pocket entrance. Fold the sacking into wrong side and topstitch pocket entrance at 0.5 cm from the edge. Mark pocket's place on large sacking. Lay side front part to marking. Stitch sacking's lower edges together and neaten them. Fix the pocket along side edges.

3. Stitch side front skirt to center skirt. Neaten the seam and press it toward center front part. Topstitch the detail at 0.5 cm from seam.
4. Make loops for cord in the middle of center back skirt. Cut fabric coulisse at 45 degree. Neaten the coulisse along the contour. Mark place of coulisse into center back skirt. Topstitch coulisse's long edges on center back skirt. Pull the cord into coulisses and eyelets.
5. Stitch side back skirt to center skirt. Neaten the seam and press it toward center skirt.
6. Stitch the yoke to back skirt. Press the seam toward back yoke. Stitch the yoke to front skirt. Press the seam toward front yoke.
7. Neaten side edges of front/back skirts. Stitch skirt's side seams leaving a slit into left seam (for zipper). Press side seams pressing closure slit. Stitch the zipper in.
8. Stitch facings' side edge and press the seam apart. Neaten facings' outer edge.
9. Lay facings on skirt's upper edge right sides together, then overstretch. Topstitch overstretching on doubled yokes at 0.2 cm from overstretching. Fold facings' into wrong side and press overstretched upper edge of the skirt. Fold side edges of back facings under and sew them to zipper. Topstitch neaten edge of facings on the seam joining yokes. Remove tacking.
10. Neaten the hem, fold it under and topstitch.

TECHNICAL DRAWING:

