

## Sewing Pattern — Dress 5560

Recommendations on fabric: natural or mixed fabrics suitable for dresses.

You will also need: blind zipper, fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem – 3 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Back part yoke – 4 details
4. Front part yoke – 2 details
5. Side front part – 2 details
6. Upper front part – 2 details
7. Central front part – 2 details

**Fusing:** front part yoke, back part yoke

### **INSTRUCTIONS:**

1. Apply fusing to front part yoke, and back part yoke.
2. Sew and serge center seam of central front part. Press center edge onto right front part and put decorative stitch by 0.5 cm off the seam.
3. Stitch side part of front part to central part of front part. Serge and press the seam onto central front part. Put decorative stitch by 0.5 cm off the seam.
4. Stitch upper front part to side front part. Serge and press the seam onto upper front part. Put decorative stitch by 0.5 cm off the seam.
5. Stitch yoke to front part. Serge and press the seam onto front part. Put decorative stitch by 0.5 cm off the seam.

6. Stitch side back part to central part. Serge and press the seam onto central back part. Put decorative stitch by 0.5 cm off the seam.
7. Stitch yoke to back part. Serge and press the seam towards back part. Put decorative stitch by 0.5 cm off the seam.
8. Serge center edge of back part. Sew center seam of back part up to the zipper notch. Press apart center seam of back part, pressing slits for zipper. Sew in zipper.
9. Sew and serge shoulder edges of the dress. Press shoulder seams onto back part.
10. Sew and serge side edges of the dress. Press side seams onto back part.
11. Sew shoulder and side edges of fused yokes of front part and of back part, press seams apart. Serge outer edge of yokes. Fold details of yokes with the garment right sides touching and overstretch neckline edge of front part and of back part. Overstretch armhole in two steps: first upper edge of the armhole, then lower edge of the armhole. Stitch center edge of back part yoke to zipper allowance. Topstitch seam allowance onto yoke by 0.2 cm off the seam. Turn the facing onto wrong side and press.
12. Serge, turn inside and topstitch hem of the garment.

**TECHNICAL DRAWING:**

