

Sewing Pattern — Dress 4228

Recommendations on fabric: dress fabric of natural or mixed fibers with elastane.

You will also need: separable zipper (of back part middle seam length), fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem and hem of sleeve – 2.5 cm, all other seams 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

ATTENTION: Lining details are cut as main fabric details except for the width of back part neckline facing and buttonstand correspondingly.

CUTTING:

Main fabric 1:

1. Central back part – 2 details
2. Central front part – 1 detail
3. Side lower front part – 2 details
4. Front part of sleeve — 2 details
5. Back part of sleeve — 2 details

Main fabric 2:

1. Upper front part – 1 detail
2. Central part of sleeve — 2 details
3. Inset of front part — 2 details
4. Inset of back part — 2 details
5. Upper back part – 2 details
6. Front neckline facing — 1 detail
7. Back neckline facing — 2 details



INSTRUCTIONS:

1. Apply fusing to facings.
2. Stitch upper part of front part to central part. Serge and press downwards. Stitch inset to of side front part. Serge and press downwards. Stitch side part to central. Slash the corner away and serge. Press Seam allowance towards center, and on sloping section — downwards.
3. Slash seam allowance of the dart on central part of back part towards the top at 1 — 1.5 cm. Stitch inset of back part. Serge and press downwards. Sew darts of back part. Stitch upper part to back part. Serge and press downwards.
4. Serge middle edge of back part. Stitch separable zipper to back part.
5. Sew side and shoulder edges. Serge and press towards back part.
6. Sew shoulder seams of the facing. Press apart the seam. Serge facings along outer edge. Overstitch the neckline with facing. Slash seam allowances, turn onto right side and press. Fasten facings to shoulder seams by hand. Tack the ends of the facings to zipper.
7. Sew sleeve details. Serge and press from center. Sew sleeve into the armhole.
8. Serge lower edge of the dress and of sleeve. Turn onto wrong side, press and topstitch.

TECHNICAL DRAWING:

