

Sewing Pattern — Jacket 5546

Recommendations on fabric: natural/mixed fabric

You will also need: fusing; 3 buttons; lining; shoulder pads

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for garment/sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side lower front part – 2 pieces
4. Side upper front part – 2 pieces
5. Center upper front part – 2 pieces
6. Center lower front part – 2 pieces
7. Middle lower front part – 2 pieces
8. Middle upper front part – 2 pieces
9. Front band – 2 pieces
10. Inner collar – 1 piece
11. Outer collar – 1 piece
12. Upper sleeve – 2 pieces
13. Lower sleeve – 2 pieces
14. Back neckline facing – 1 piece

Lining:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side lower front part – 2 pieces
4. Side upper front part – 2 pieces
5. Center upper front part – 2 pieces

6. Center lower front part – 2 pieces
7. Middle lower front part – 2 pieces
8. Middle upper front part – 2 pieces
9. Upper sleeve part – 2 pieces
10. Lower sleeve – 2 pieces

Fusing: front band, outer collar, back neckline facing, center upper front part, center lower front part, middle upper front part, middle lower front part, side upper front part, side lower front part.

INSTRUCTIONS:

1. Apply the fusing to front band, outer collar, back neckline facing, center upper front part, center lower front part, middle upper front part, middle lower front part, side upper front part, side lower front part.
2. Lay outer collar on inner one and overstretch. Cut seams at corners, turn right side out and press the collar.
3. Stitch middle lower front part to center lower front part. Press joining seam and topstitch at 0.5 cm from seam. Stitch side lower front part to middle lower front part. Press joining seam apart and topstitch at 0.5 cm from seam. Stitch middle upper front part to center upper front part. Press joining seam and topstitch at 0.5 cm from seam. Stitch side upper front part to middle upper front part. Press joining seam apart and topstitch at 0.5 cm from seam. Stitch upper front part to lower front part. Press joining seam apart and topstitch at 0.5 cm from seam.
4. Pin front band on front part right sides together and overstretch along shaped edging. (Overstretch front part towards the notch that determines where stitching the collar in stops.) Stitch lower edges of front bands to front part along marked hem line. Cut seams of upper/lower corners of edging. Topstitch edging's overstretching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
5. Stitch back relieves and press them apart. Topstitch at 0.5 cm from seam. Stitch middle back seam and press it apart.
6. Stitch shoulder/side seams.
7. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing.
8. Stitch elbow seam and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seam and press it apart.
9. Stitch sleeve into armholes. Sew shoulder pads
10. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve and waistband hole into left side seam.
11. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
12. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.
13. Make buttonholes into right front edging, sew buttons on left one.

TECHNICAL DRAWING:

