

Sewing Pattern — Jacket 5545

Recommendations on fabric: wool/semi-wool

You will also need: fusing; 3 buttons; lining; shoulder pads.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams, 3.5 cm for garment/sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Center front part – 2 pieces
5. Middle front part – 2 pieces
6. Front band – 2 pieces
7. Inner collar – 1 piece
8. Outer collar – 1 piece
9. Upper sleeve – 2 pieces
10. Lower sleeve – 2 pieces
11. Pocket – 2 pieces
12. Front flap – 4 pieces
13. Back neckline facing – 1 piece

Lining:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Center front part – 2 pieces
5. Middle front part – 2 pieces
6. Upper sleeve – 2 pieces

7. Lower sleeve – 2 pieces
8. Closure lining – 2 pieces

Fusing: front band, outer collar, back neckline facing, closure lining, center front part.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, outer collar, back neckline facing, closure lining, center front part.
2. Lay flaps on under-flaps right sides together, then overstretch. Cut allowances of flaps' corners, then turn them right side out. Neaten flaps' free edges. Press flaps. Lay outer collar in lower one, then overstretch. Press the collar.
3. Stitch middle front part to center front part. Press the seam apart. Stitch side front part to middle front part. Press the seam apart.
4. Mark pocket place. Stitch pocket lining to pocket's upper edge and stitch pocket/lining edges together along the contour leaving a hole of 5 cm length into side seam (to turn the pocket right side out.) Cut allowances of rounded corners and turn the pocket right side out. Press the pocket. Topstitch the pocket in accordance with marking. Mark flap place. Stitch the flap on marking. Fold the flap downwards and topstitch at 0.5 cm from joining seam.
5. Mark closure slit into right front band with three lines: the first line is parallel to edgings and goes at 2 cm from edging as ready; the second and the third lines limit closure length. Lay reinforced facing on front band right sides together coinciding facing's edge and marked line. Make a stitch at 0.5 cm from closure slit up to lines that limit closure length. Lay closure's second facing to the stitch joining the first facing so that facings meet, and make a stitch at 0.5 cm distance. Check if facings were stitched correctly (stitches on wrong side must be parallel.) Cut pocket entrance. Cut diagonal notches at 1-1.5 cm from pocket ends. Turn facings into wrong side through notches to make facings-made frame equal the width between stitches. Make fixing stitch along the seam joining the facing. Press the second facing towards front band's inner edge at 0.1 cm from the seam joining the facing. Make buttonholes. Fix closure's ends with double reverse stitch along wrong side of corners' bases. Stitch facings' edges together. Make fixing stitches between each pair of buttonholes (1 fixing stitch's length is equal to frame's width). Press front band.
6. Pin front band on front part right sides together and overstretch along edging. (Overstretch front part upward the notch determining the end of stitching the collar in). Stitch lower edges of front bands to front part along marked hem line. Cut seams of upper/lower corners of edging. Topstitch edging's overstretching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
7. Stitch middle back seam and press it part. Stitch shoulder/side seams and press them apart.
8. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing.
9. Stitch elbow seams and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seams and press them apart.

10. Stitch sleeves into armholes according to notches. Sew shoulder pads.
 11. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve.
 12. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
 13. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole.
- Stitch hole's edges together.
14. Make buttonholes into right front part, sew buttons on left one.

TECHNICAL DRAWING:

