

Sewing Pattern — Zip-Up Jacket 5543

Recommendations on fabric: wool or semi-wool.

You will also need: fusing, separating zipper, lining, shoulder pads, sleeve heads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3.5 cm for the garment hem, 3 cm for sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side back part – 2 pieces
2. Side front part – 2 pieces
3. Front band – 2 pieces
4. Collar – 2 pieces
5. Upper sleeve part – 2 pieces
6. Lower sleeve part – 2 pieces
7. Center back part – 2 pieces
8. Front yoke – 2 pieces
9. Center front part – 2 pieces
10. Back neckline facing – 1 piece

Lining:

1. Side back part – 2 pieces
2. Side front part – 2 pieces
3. Upper sleeve part – 2 pieces
4. Lower sleeve part - 2 pieces
5. Center back part – 2 pieces
6. Front yoke – 2 pieces
7. Center front part – 2 pieces

Fusing: front band, back neckline facing, upper collar, center front part.

INSTRUCTIONS:

1. Apply fusing to front band, back neckline facing, upper collar, center front part.
2. Sew center front part to side front part. Press the seams apart.
3. Sew the yoke to the front part. Press the seam apart.
4. Put collar parts together wrong side out and overstitch. Neaten the seam and press the collar.
5. Stitch and press apart the back curved seams. Stitch and press apart the middle seam.
6. Put the front parts together wrong side out and align them according to the buffet lengths. Stitch separating zipper to the buffet edge. Fold buffet edge at the zipper stitching area and press.
7. Rut front band and front part together wrong side out, pin and overstitch along the buffet. Make overdtitching on the side of the front part. Stitch front band lower edges to the front part exactly on the marked line of hem turning allowance. Cut seam allowances at the lower buffet corners. Turn the buffets out on the right side, neaten the seams. Make a decorative stitch along the buffet edge at 0.5 cm from the edge.
8. Sew and press apart the jacket shoulder and side seams.
9. Sew and press apart the back neckline and band facing shoulder seams. Stitch the lower collar into the jacket neckline edge. Stitch upper collar into the neckline edge of the back neckline and front band facings.
10. Sew and press apart the outside sleeve seam. Sew and press apart the underarm sleeve seam. Fold and press the sleeve hem.
11. Sew the sleeve into the armhole coinciding notches. Stitch in the shoulder pads and sleeve heads.
12. Sew together the parts from the lining and stitch in the sleeves, leaving a slit in the right sleeve underarm seam.
13. Stitch the lining to the front band and back neckline facing inner edges. Press apart collar attaching seam allowances and fasten close to the seams.
14. Stitch the lining to the jacket and sleeve hems. Turn the jacket out on to the right side through the slit in the lining sleeve seam. Stitch the slit.

TECHNICAL DRAWING:

