

Sewing Pattern — Jacket 5542

Recommendations on fabric: wool/semi-wool

You will also need: fusing; lining; shoulder pads; 5 buttons; 3 zippers (for pockets)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2,5 cm for garment/sleeve hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side back part – 2 pieces
2. Side front part – 2 pieces
3. Front band – 2 pieces
4. Collar – 2 pieces
5. Center back part – 2 pieces
6. Right center front part – 1 piece
7. Left center front part – 1 piece
8. Upper pocket's facing – 2 pieces
9. Upper pocket's large facing – 1 piece
10. Sleeve – 2 pieces
11. Cuff – 2 pieces
12. Back neckline facing – 1 piece
13. Pocket's large facing – 2 pieces
14. Placket – 1 piece

Lining:

1. Side back part – 2 pieces
2. Side front part – 2 pieces
3. Center back part – 2 pieces
4. Center front part – 2 pieces
5. Sleeve – 2 pieces

6. Upper pocket's small lining – 1 piece
7. Pocket's small lining – 2 pieces

Fusing: front band, back neckline facing, reinforcement, outer collar, center front part

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, back neckline facing, outer collar, center front part
2. Mark placket's place on left front part. Press placket's side edges under and topstitch the details on left front part in accordance with marking.
3. Stitch back darts and press them towards the center.
4. Lay outer collar on inner one and overstretch them. Press the collar.
5. Stitch front relieves and press them apart.
6. Mark lower/upper pockets' place. Apply the reinforcement stripe at pockets' entrances. Press pocket facings along the center right side out. Mark auxiliary line parallel facing's bending. Mark auxiliary lines parallel pocket entrance for stitch the flap and pocket facings to (front part). Stitch facings to front part. Stop stitching at parallel lines of pocket marking. Check if facings were stitched correctly (stitches on wrong side must be parallel.) Cut pocket entrance. Cut diagonal notches at 1-1.5 cm from pocket ends. Turn facings into wrong side through notches to make facing's pressed bendings meet. Make double reverse stitches on pocket ends' wrong side (along corner's bases.) Stitch the zipper in. Stitch pocket's large lining to pocket's upper facing. Stitch pocket's small lining into the seam joining lower facing; cut, then stitch pocket's linings together. Do the same for upper/lower pockets.
7. Cut fabric stripe of 3 cm width for loops. Fold the stripe along the center and topstitch at 0.5 cm from bending overstretching one end. Turn the stripe right side out and press it. Cut the stripe and fold pieces to make loops. Tack loops to right front part according to marks.
8. Pin front band on front part right sides together and overstretch along edging. Stitch lower edges of front bands to front part along marked hem line. Cut seams of lower corners of edging. Topstitch edging's overstretching allowance on front band at closure (stop stitching 3 cm before neckline and lower corner). (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
9. Stitch back relieves and press them apart. Stitch middle back seam and press it apart. Stitch shoulder/side edges and press seams apart.
10. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing/front band.
11. Press the cuff along the center right side out. Stitch cuff's side edge, press side seam apart. Press the cuff along the center. Stitch sleeve seam and press it apart. Stitch cuffs to sleeve's lower hems.
12. Stitch sleeves into armholes according to notches. Sew shoulder pads.

13. Stitch lining details together and stitch sleeve in, leaving a hole into sleeve seam.
14. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
15. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.
16. Sew buttons on left front part.

Our advice: Take raglan shoulder pads to make slope shoulders. The length of 1 loop is $2 \times \text{button's diameter} + 4$.

TECHNICAL DRAWING:

