

## Sewing Pattern — Jacket 5539

Recommendations on fabric: wool/semi-wool

You will also need: fusing; 1 button; lining; shoulder pads

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for garment/sleeve hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Inner collar – 1 piece
2. Outer collar – 1 piece
3. Side front part – 2 pieces
4. Flap – 4 pieces
5. Front band – 2 pieces
6. Back neckline facing – 1 piece
7. Side back part – 2 pieces
8. Center back part – 2 pieces
9. Center front part – 2 pieces
10. Upper sleeve – 2 pieces
11. Lower sleeve – 2 pieces

Lining:

1. Center front part – 2 pieces
2. Side back part – 2 pieces
3. Center back part – 2 pieces
4. Side front part – 2 pieces
5. Upper sleeve – 2 pieces
6. Lower sleeve – 2 pieces
7. Small pocket – 2 pieces
8. Large pocket – 2 pieces

Fusing: front band, reinforcement stripe, center front part, jacket/sleeve hems, back neckline facing, outer collar, flap.

### **INSTRUCTIONS:**

1. Apply the fusing to front band, center front part, jacket/sleeve hems, back neckline facing outer collar, flap.
2. Stitch back darts and press them towards the center. Stitch front darts, slash darts' depths and press them apart.
3. Lay flaps right sides together, then overstitch. Cut allowances of flap corners and turn them right side out. Press seams.
4. Fix pocket entrance with reinforcement stripe or tack it together. Stitch front/back relieve seams and press them apart.
5. Cut facing of side slit pocket and apply the reinforcement stripe at pocket entrance. Mark pocket place. Press pocket facings along the center right side out. Mark auxiliary line parallel facing's bending. Mark auxiliary line parallel to flap's upper edge measuring flap's width along its length. Mark auxiliary lines parallel pocket entrance for stitch the flap and pocket facings to. Stitch pocket lining to flap. Stitch facings to front part. Stop stitching at parallel lines of pocket marking. Check if facings were stitched correctly (stitches on wrong side must be parallel.) Cut pocket entrance. Cut diagonal notches at 1-1.5 cm from pocket ends. Turn facings into wrong side through notches to make facing's pressed bendings meet. Make double reverse stitches on pocket ends' wrong side (along corner's bases.) Insert the flap into pocket and stitch it to pocket's upper facing. Stitch pocket's lower lining along the seam joining lower facing, cut it and stitch pocket lining.
6. Lay outer collar on lower one, then overstitch. Cut seams at corners, turn right side out, then press the collar.
7. Pin front band on front part right sides together and overstitch along edging. (Overstitch front part upward the notch determining the end of stitching the collar in). Stitch lower edges of front bands to front part along marked hem line. Cut seams of upper/lower corners of edging. Topstitch edging's overstitching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
8. Stitch middle back seam and press it apart. Stitch shoulder/side edges, then press seams apart.
9. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing/front band.
10. Stitch elbow seams and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seams and press them apart.

11. Stitch sleeves into armholes according to notches. Sew shoulder pads.
12. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve.
13. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
14. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.
15. Make a buttonhole into right front edging, sew the button on left one.

**TECHNICAL DRAWING:**

