

## Sewing Pattern — Dress 5534

Recommendations on fabric: natural or mixed fabric

You will also need: zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Right center back part – 1 piece
2. Left center back part – 1 piece
3. Right side back part – 1 piece
4. Left side back part – 1 piece
5. Right side front part – 1 piece
6. Right center front part – 1 piece
7. Left center front part – 1 piece
8. Left side front part – 1 piece
9. Gusset – 4 pieces
10. Flounce of gusset – 4 pieces
11. Upper flounce\_1 – 1 piece
12. Upper flounce\_2 – 1 piece

### **INSTRUCTIONS:**

1. Neaten lower edges of flounces, gussets and dress details with roll stitches.
2. Adjust side edges of the gusset and flounce of russet and tack them together.
3. Stitch the gusset to right center front part, neaten joining seam 4 cm above the notch. Stitch middle front edge and gusset side edge. Press middle front seam pressing the gusset. Remove tacking.

4. Stitch front/back relieve edges. Neaten front/back relieve seams, press front seams towards front center, press back seams towards back center.
5. Stitch the gusset to left center back part, neaten joining seam. Neaten middle edge of left center back part with the gusset and middle edge of right center back part. Stitch middle back edge to gusset side edge up to closure notch. Press middle back edge apart, press slits. Remove tacking. Stitch the zipper in.
6. Stitch the gusset to side back part, neaten joining sea 4 cm above notch. Stitch side seam and gusset side edge. Remove tacking. Press dress side seams.
7. Neaten shoulder seam of the dress, stitch it and pres it apart.
8. Cut shoulder strap. Fold the strap along the center wrong side out and make a stitch at 0.5 cm from fold. Turn the strap right side out and press. Sew the strap to front neckline.
9. Try the dress, adjust strap length and sew back end on back part.
10. Stitch side edge of upper flounce and neaten it. Overstitch the edge of neckline and armhole with the flounce. Neaten oversteitching seam and topstitch on the dress at 0.2 cm from oversteitching.

#### **TECHNICAL DRAWING:**

