

Sewing Pattern — Dress 5521

Recommendations on fabric: natural/mixed fabric
You will also need: trim fabric with elastic thread, 25 cm
zipper, bias tape, elastic braid

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Trim – cut 2
2. Center back – cut 2
3. Side back – cut 2
4. Side front – cut 2
5. Center front – cut 1

INSTRUCTIONS:

1. Press the bias tape along the center and pin to armhole edges, right sides together, and sew. Trim seams, turn onto wrong side, and sew along fold onto main garment.
2. Sew side fronts to front and side backs to backs. Serge and press seams toward center.
3. Sew side seams. Serge and press seams toward back.

4. Sew pleats into outer layer of front trim. Lay trim right sides together and sew upper edge. Try the trim on, adjust, and topstitch elastic braid on sides. Sew trim to front/back upper edge. Serge joining seam, press, and topstitch at 0.5 cm from edge.
5. Serge center back/trim edges separately. Sew center back seam from zipper mark to lower edge of garment. Press seam apart, as well as opening for zipper. Sew in zipper.
6. Serge lower edge of garment, turn onto wrong side, topstitch at 0.5 cm from edge.

TECHNICAL DRAWING:

