

Sewing Pattern — Dress 5515

Recommendations on fabric: natural/mixed fabric.

You will also need: zipper of 25 cm length, piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper back part – 2 pieces
2. Lower back part – 2 pieces
3. Lower front part – 2 pieces
4. Upper front part – 2 pieces
5. Front insert – 2 pieces
6. Skirt insert – 1 piece

INSTRUCTIONS:

1. Press front insert along the center. Stitch the insert to upper front part, neaten it and press upwards.
2. Stitch skirt insert to lower front part. Neaten joining seam and press it downwards.
3. Make a stitch with weak loops along skirt insert's upper edge at 0.5 cm from edge; make gathering. Stitch upper front part to lower front part. Neaten joining seam and press it downwards.
4. Stitch upper back part to lower back part. Neaten joining seam and press it downwards.

5. Press the piping along the center; overstretch front/back armholes' edge and back neckline edge.
6. Neaten middle back edge. Stitch middle back seam up to closure notch. Press middle back seam apart, press closure slits. Stitch the zipper in.
7. Stitch dress side/shoulder edges. Neaten side/shoulder seams and press them backwards.
8. Neaten the hem, fold it under and topstitch at 0.5 cm from lower edge.

TECHNICAL DRAWING:

