

## Sewing Pattern — Skirt 5508

Recommendations on fabric: natural/mixed fabric.

You will also need: fusing; 1 zipper of 20 cm length; 1 button; elastic braid

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1 cm, 3 cm for garment hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Middle back panel – 2 pieces
2. Side back panel – 2 pieces
3. Waistband – 1 piece
4. Middle front panel – 1 piece
5. Side front panel – 2 pieces

Fusing: waistband.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of waistband.
2. Neaten side edges of middle front panel, side front panel, middle back panel and side back panel.
3. Stitch front panel's relieve seams and press them apart. Stitch back panel's relieve seams and press them apart.
4. Neaten back middle edge. Stitch back middle seam up to closure slit notch. Press back middle seam apart and press slits for zipper.

5. Stitch the zipper into skirt middle seam. Stitch garment side seams apart.
6. Press the waistband along the center right side out and neaten waistband's lower inner edge.
7. Cut elastic braid according to size. Fix it at waistband's sides. Topstitch elastic braid stretching it along the waist. Stitch the waistband to garment upper edge and overstitch waistband corners. Topstitch waistband lower edge on seam joining the waistband.
8. Neaten garment hem, press it into wrong side and topstitch on the garment.

**TECHNICAL DRAWING:**

