

Sewing Pattern — Shirt 5505

Recommendations on fabric: fabric suitable for blouse.

You will also need: fusing, 10 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for garment hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Yoke – 1 piece
2. Back part – 2 pieces
3. Front part – 2 pieces
4. Collar – 2 pieces
5. Stand-up collar – 2 pieces
6. Front band – 2 pieces
7. Cuff – 2 pieces
8. Sleeve – 2 pieces
9. Flap – 4 pieces
10. Pocket – 2 pieces

Fusing: front band, outer collar, stand-up collar, cuff.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, outer collar, stand-up collar, cuff.
2. Stitch front darts. Press them downwards.

3. Neaten front band inner edge.
4. Lay flap details right sides together and overstitch them. Cut allowances into corners and turn them right side out. Make decorative stitch along flap outer corner at 0.5 cm from edge and neaten flap upper edge.
5. Neaten pocket outer contour and press it according to pattern. Topstitch upper edge on the pocket; topstitch the pocket along the contour at 0.2 cm from pocket edge. Topstitch the flap according to marks. Fold the flap towards right side and topstitch it at 0.5 cm from the seam.
6. Stitch back middle seam and neaten it apart. Press back middle edge rightwards.
7. Stitch the yoke to front part. Neaten joining seam and press it towards front part.
8. Overstitch edgings with front bands, slash extra fabric in corners and turn front bands right sides out. Press edgings.
9. Stitch the yoke to back part. Neaten joining seam and press it backwards. Stitch garment side edges and neaten them. Press garment side edges backwards.
10. Make a slit into a sleeve. Press the piping along the center. Trim the slit with piping, make a stitch at slit top corner. Stitch sleeve edge and neaten it. Press sleeve edge. Make pleats along sleeve hem between notches.
11. Stitch sleeves in.
12. Overstitch inner collar with outer one, turn the collar right side out. Press the collar.
13. Stitch stand-ups together, inserting the collar between them. Press stand-up collar.
14. Stitch inner stand-up with collar into neckline. Fold outer stand-up open edge and topstitch it along the seam joining inner stand-up.
15. Overstitch cuff side edges and turn the cuff right side out. Press ready cuff.
16. Stitch outer cuff to sleeve lower edge. Fold inner cuff under and topstitch.
17. Neaten garment hem, fold it out and topstitch.
18. Make buttonholes into right front part, sew buttons on left one.

TECHNICAL DRAWING:

