

Sewing Pattern — Coat 5490

Recommendations on fabric: artificial/nature leather.

You will also need: fusing; separable; lining; 4 zippers for pocket.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams. 3,5 cm for garment hem, 3 cm for lower pocket sleeve hems. 0 cm for upper pocket side/lower edges, for upper/lower/inner edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back belt – 1 piece
2. Right front belt – 1 piece
3. Left front belt – 1 piece
4. Belt facing – 1 piece
5. Tie – 4 pieces
6. Belt loop – 1 piece
7. Center back part – 2 pieces
8. Side back part – 2 pieces
9. Side front part – 2 pieces
10. Center front part – 2 pieces
11. Upper pocket – 2 pieces
12. Lower pocket – 2 pieces
13. Front band – 2 pieces
14. Upper sleeve – 2 pieces
15. Lower sleeve – 2 pieces
16. Cuff – 4 pieces
17. Back neckline facing – 1 piece

Lining:

1. Center back part – 2 pieces
2. Side back part – 2 pieces

3. Front part – 2 pieces
4. Upper sleeve – 2 pieces
5. Lower sleeve – 2 pieces

Fusing: front band, back neckline facing, reinforcement stripe, belt facing

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, back neckline facing, reinforcement stripe, belt facing.
2. Stitch front darts. Slash dart depth and press darts apart. Make decorative stitch along darts. Stitch front relieve edges and press them. Make decorative stitches along relieves.
3. Stitch back relieve edges and press them. Make decorative stitches along relieves. Stitch middle back edge and press it. Make decorative stitch along middle seam.
4. Mark upper pocket on front part. Press allowance of pocket upper edge into wrong side and make a double stitch along it. Cut the pocket along marked line. Lay the zipper under slit edges with zipper's teeth visible, then topstitch. Topstitch upper pocket on front part with a double stitch.
5. Mark lower pocket on front part. Reinforce pocket entrance with reinforcement stripe. Check pocket place and pocket entrance line. Cut pocket entrance. Make diagonal slits at 1-1.5 cm from pocket ends. Turn pocket allowance wrong side out through this hole. Check pocket end on wrong side. Lay the zipper under pocket entrance edge with its teeth visible. Sew the zipper in. Topstitch lower pocket on front part along upper/inner/lower edges.
6. Fold the tie along the center right side out, fold long edges' allowances under and make decorative stitch along tie contour at 0.2 cm from edge. Do the same for belt loop stripe. Cut belt loops according to marks.
7. Stitch belt details together inserting tie according to marking. Lay belt facing on right front belt right sides together and overstitch them. Cut corner allowances and turn the belt right side out. Press upper allowance into wrong side and make decorative double stitch. Topstitch belt loops on the belt according to marks.
8. Lay front parts right sides together and adjust edges measuring edging lengths. Stitch the zipper to edging. Press edging under at closure segment.
9. Stitch shoulder/side edges and press them apart.
10. Stitch shoulder edges of front band and facing and press them apart. Lay front band on front part right sides together and overstitch along edging and back neckline (on front part side). Overstitch front part lower corner, cut corner allowances, slash at curve segments of seam. Turn front bands right side out and press seams. Make decorative stitch along edging and neckline at 0.5 cm from edge.
11. Lay the belt on the garment according to marks. Topstitch the belt along side/middle seams and along edging decorative stitch.

12. Stitch sleeve front edge and press it apart. Stitch cuffs to sleeves, press allowances towards sleeves. Stitch elbow edges and press them apart. Press sleeve hems under. If you wish, you can make decorative stitches at equal distance on cuffs.
13. Stitch sleeves into armholes according to notches.
14. Sew lining details together and sew sleeves in, leaving a hole into sleeve right front seam. Press lining allowances under. Stitch the lining to inner edges of front band and back neckline facing.
15. Press garment hem under. Overstitch sleeve hems and garment hem with lining. Fix the lining to garment at waist seams. Turn the garment right side out through the hole in sleeve. Stitch sleeve hole edges together.

TECHNICAL DRAWING:

