

Sewing Pattern — Skirt 5481

Recommendations on fabric: denim.

You will also need: fusible interfacing, skirt zipper.

If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: 1 cm on all edges, 2 cm on hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Fabric:

1. Skirt Panels – cut 4 (cut all 4 pieces the same way on the same side of the fabric)
2. Facing – cut 2 of fabric, cut 2 of interfacing

INSTRUCTIONS:

1. Apply the interfacing to wrong side of facings.
2. Sew all panels together leaving opening for zipper unstitched on left side. Serge or pink zipper edges in left side seam.
3. Sew side edges of facings and press seams open. Leave left side open. Finish bottom edge of facing.
4. Sew facing to skirt waistline, right sides together. Press seam up towards facing.
5. Apply zipper according to zipper instructions. Top of zipper teeth should line up to waistline seam allowance.
6. Turn facing to inside. Fold under facing edges and slip-stitch to zipper.
7. Top-stitch upper edge of skirt.

8. Tack facing by hand to inside seams.
9. Finish bottom edge, turn under, hem with a topstitch, or as desired.

TECHNICAL DRAWING:

