

Sewing Pattern — Jacket 5475

Recommendations on fabric: artificial/natural leather.

You will also need: fusing, 9 buttons, lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams. 0 cm for garment hem, front part edge and front band, collar flying part up to stitching in mark, for yoke outer edge, pocket upper/side/lower edges, for garment hem facing lower edges, for cuff side/lower edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center lower back facing – 1 piece
2. Side lower back facing – 2 pieces
3. Front lower facing – 2 pieces
4. Patch pocket – 2 pieces
5. Yoke – 2 pieces
6. Center back part – 2 pieces
7. Side back part – 2 pieces
8. Inner collar – 1 piece
9. Outer collar – 1 piece
10. Side front part – 2 pieces
11. Center upper front part – 2 pieces
12. Center lower front part – 2 pieces
13. Front band – 2 pieces
14. Back neckline facing – 1 piece
15. Yoke pocket facing – 2 pieces
16. Patch pocket facing – 2 pieces
17. Sleeve – 2 pieces
18. Cuff – 4 pieces

Lining:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Center upper front part – 2 pieces
5. Center lower front part – 2 pieces
6. Sleeve – 2 pieces

Fusing: front band, pocket facing, back neckline facing, lower front facing, lower back facing, aides facing.

INSTRUCTIONS:

1. Apply the facing to wrong side of front band, pocket facing, back neckline facing, lower front facing, lower back facing, aides facing.
2. Mark darts on front/back parts. Stitch back darts and press them towards the center. Stitch front darts and slash depths. Make decorative stitch at 0.2 cm from darts.
3. Sew upper front detail to lower front detail. Press allowance upwards. Sew side front part to center front part and press the seam apart.
4. Lay yoke pocket facing on the yoke right sides together, then sew them together along marked lines. Check whether facing is stitched correctly (on wrong side, stitches must be parallel to each other, the distance between them is ready facing double width). Slit pocket entrance. Make diagonal slits at 1-1.5 cm from pocket ends. Turn pocket facing wrong side out through this hole. Fix pocket ends on wrong side with reverse double stitch along base of corners. Make decorative stitch along pocket entrance. Lay yoke's wrong side on front part's right side and topstitch it along outer contour.
5. Process slit pocket on patch pocket by analogy. Lay patch pocket's wrong side on lower front part's right side and topstitch along three sides.
6. Sew middle back seam and press it. Sew back relieves and press them. Make decorative stitch along seams. Sew side/shoulder seams and press them apart.
7. Sew back neckline facing to front bands. Stitch outer collar into jacket neckline, stitch inner collar into facing neckline.
8. Lay front band with collar on front part wrong sides together, pin, and stitch along edging and collar. Press collar joining seam allowances apart and fix them close to seams.
9. Fold cuffs right side out and topstitch along thee sides. Fold a cuff in a ring along marked line, and fix. Sew cuffs to sleeves, press seams towards sleeves. Make decorative stitch along seams joining cuffs. Sew sleeves into armholes according to notches.

11. Sew lower front facing, lower back facing and side facing together. Press seams apart. Sew darts into lining details, sew seams and sew sleeves into armholes. Press lining allowances. Sew hem facing to lining. Press the seam towards the lining. Sew the lining to front band inner edges and neckline facing. Turn the jacket right side out.

12. Coincide jacket hem and facing hems and topstitch. Turn lining sleeve hem under and topstitch.

13. Make buttonholes into right front part and sew buttons on left one. Sew buttons to sleeve cuffs.

TECHNICAL DRAWING:

