

Sewing Pattern — Sarafan (Sleeveless Dress) 5474

Recommendations on fabric: soft flax or mixed fabric.

You will also need: piping; zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Back facing – 2 pieces
3. Front part – 1 piece
4. Front facing – 1 piece

INSTRUCTIONS:

1. Overstitch front neckline edge with front facing. Topstitch overstitch allowance on overstitching at 0.2 cm from overstitching. Mark coulisse line on front part.
2. Overstitch back neckline edge with back facing. Topstitch overstitch allowance on overstitching at 0.2 cm from overstitching. Mark coulisse line on back part.
3. Mark front/back darts and sew them. Press darts toward front/back centers.
4. Neaten back middle edge. Sew edges of back middle and facing, leaving a slit for zipper. Press back middle seam apart and press closure edges. Sew the zipper in.
5. Sew dress side edges and neaten them. Press side allowances backwards.
6. Press the piping along the center. Overstitch front/back armhole edges and side edges of front/back facings with piping. Neaten front/back facing's outer edges.
7. Cut out ties out of fabric. Fold ties along the center and topstitch them at 0.5 cm from bending. Turn ties right side out and press them. Pull short ends of ties in and sew by hand. Topstitch facings along marking and pull ties in.
8. Neaten garment hem, press it to wrong side and topstitch.

TECHNICAL DRAWING:

