

Sewing Pattern — Shorts with Cord 5471

Recommendations on fabric: flax.

You will also need: fusing, decorative cord.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for upper edge, 3 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Flap – 2 pieces
4. Belt loop – 1 piece

Fusing: flap.

INSTRUCTIONS:

1. Apply the fusing to wrong side of flap.
2. Lay flap details right sides together and overstretch. Slash allowances in corners, and turn right side out. Make decorative stitch along flap outer contour at 0.5 cm from edge. Neaten flap upper edge. Mark flap place and topstitch flap along marking. Fold the flap to right side and topstitch it at 0.5 cm from seam.
3. Neaten side/inside leg edges of front/back parts, front middle edge, fly front edge and back middle edge.
4. Fold belt loop along the center, right side together, coincide edges and overstretch at 0.5-0.7 cm from edges. Turn right side out, place the seam at fold or make edging of 0.1-0.2 cm width to wrong side, and press.
5. Sew side/inside leg seams, and press them apart. Sew fly front edge and middle sitting edge.
6. Neaten garment upper edge. Press garment upper edge to wrong side. Topstitch allowance. Mark place of belt loops. Cut belt loops of proper size and topstitch according to marks.

7. Neaten hem allowance and press to wrong side. Topstitch hem allowance. Pull decorative cord into belt loops.

TECHNICAL DRAWING:

