

Sewing Pattern — Blouse 4220

Recommendations on fabric: natural or mixed blouse fabrics.

You will also need: fusing; 8 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on panel – 4 cm, along neckline — 0 cm, all other seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.



When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Back part - 2 details
2. Front part - 1 folded detail
3. Lower front part - 1 folded detail
4. Lower back part — 2 details
5. Bow - 2 details
6. Sleeve – 2 details
7. Cuff – 2 details

Fusing:

1. Panel – 2 details
2. Cuff – 2 details

INSTRUCTIONS:

1. Apply fusing to one-piece panels and cuffs.
2. Sew darts on details of front part and of back part. Cut depths with serger and press the seam towards center.
3. Sew shoulder and side seams. Serge and press to back part.
4. Sew side seams of lower parts. Serge and press. Stitch loosely on top edge of lower part and gather ruffles. Serge lower edge, turn inside and topstitch. Sew top and lower parts of the blouse. Serge and press upwards.
5. Slash seam allowances on bow details near markers. Serge seam allowances along long sides, turn inside and topstitch. Fold bow detail along marker "fold" («сгиб») and overstitch on top and lower edges. Cut corners and turn details onto right side. Put details of bows, one onto another and sew

through along marker "fold" («сгиб»). Cut a strap of 6 cm wide and 10 cm long. Serge short sides, turn inside and topstitch. Turn strap around bow and fix with hand stitches. Stitch loosely along marker "side" («бок») and along middle edge of back part and gather ruffles. Stitch the bow according to marker "side" («бок») to the blouse. Fasten bows to darts with hand stitches.

6. Level middle edge of back part to middle edge of the bow. Turn one-piece panel (with bow panel) onto wrong side and press. Turn seam allowance inside and topstitch the panel.

7. Slash slit of sleeve according to marker. Cut bias tape of 4 cm wide and, the length should be equal to slit double length + 3 cm. Press bias tape in half lengthwise, turn outer edges towards center and press again. Overstitch slit with bias tape. Sew edge of sleeve, serge and press apart. Fold cuff in half lengthwise right sides together and sew side edges and overstitch the corner. Turn detail onto right side, press. Stitch outer side of cuff to the sleeve, turn inside seam allowance of inner side of the cuff and topstitch into outer cuff connecting seam. Stitch loosely on rounded part and gather ruffles. Sew sleeve into armhole. Serge seam allowances and press to sleeve.

8. Cut bias tape of 4 cm wide, length is equal to neckline length + 2 — 3 cm. Press bias tape in half lengthwise, turn inside outer edges towards center and press again. Overstitch the neckline.

9. Serge hem of the garment, press onto wrong side and topstitch.

10. Serge buttonholes left back part, sew buttons on right back part. Make buttonholes and sew buttons on cuffs.

TECHNICAL DRAWING:

