

Sewing Pattern — Jacket with Cord 5470

Recommendations on fabric: flax or mixed fabric.

You will also need: eyelets, zipper, decorative cord.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams. 3 cm for garment hem and sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Flap – 4 pieces
2. Patch pocket – 2 pieces
3. Back part – 1 piece
4. Front part – 2 pieces
5. Collar – 2 pieces
6. Front band – 2 pieces
7. Sleeve – 2 pieces

Fusing: front band, inner collar, lower flap.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front part and inner collar.
2. Lay outer collar on inner collar right sides together and overstretch inner collar with outer one. Slash, turn collar corners right side out. Press the collar.
3. Mark place of pocket and flap. Fold flap details right sides together and overstretch. Slash flaps corners allowance and turn them right side out. Make decorative stitch along flap outer contours at 0.5 cm from edge. Neaten flap upper edge.
4. Neaten pocket outer contour and press it according to pattern. Topstitch upper edge on the pocket. Topstitch the pocket along the contour at 0.2 cm from pocket edge. Topstitch the pocket along the marking. Turn the flap right side out and topstitch it at 0.5 cm from the seam.
5. Sew sleeve seam and press it apart.

6. Neaten outer edge of front band. Mark hemline. Pin front band on front part right sides together and overstretch along edging, overstretching front part up to the notch defining end of sewing in the collar. Sew lower edges of front bands to center front part strictly along marked hemline. Slash seams of upper/lower corners of front band. Turn front bands right side out and make decorative stitch at 0.2 cm from front band edge.
7. Sew side edges and shoulder edges. Neaten shoulder and side seams, press them backwards.
8. Sew the collar in the neckline. Neaten joining seam and topstitch along half-girth of back neck.
9. Sew sleeves in armholes. Neaten joining seam. Sew the zipper to front bands. Neaten garment hem and sleeve hems. Press garment/sleeves hem to wrong side and topstitch.
10. Make eyelets into sleeves and garment, pull in the cord.

TECHNICAL DRAWING:

