

## Sewing Pattern — Dress 4219

Recommendations on fabric: natural or mixed dress fabrics

You will also need: blind zipper, lace of 2. 5-3. 5 cm wide.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem of the dress – 2. 0 cm, all other seams 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Central part of the back - 2 details
2. Upper side part of the back - 2 details
3. Back part inset — 2 details
4. Lower side part of the back — 2 details
5. Lower side part of the front - 2 details
6. Lower central part of the front – 1 detail
7. Upper front part - 1 details
8. Upper side part of the front — 2 details
9. Front part inset — 1 detail
9. Front yoke - 2 details
10. Back yoke - 2 details

#### Lining:

1. Central part of the back - 2 details (up to the inset)
2. Upper side part of the back - 2 details
3. Upper part of the front - 1 details
4. Upper side part of the front — 2 details

## **INSTRUCTIONS:**

1. Sew princess edges on upper and lower parts of the front. Serge and press the seam towards center.
2. Sew side seams of upper and lower parts. Serge and press seam allowances towards back part.
3. Sew side seams of the insets. Serge and press seam allowances towards back part. Stitch inset to upper and lower parts, inserting the lace. Serge and press seam allowances upwards.
4. Sew princess seams onto back part. Serge and press seam allowances towards center.
5. Stitch yokes. Serge and press seam allowances upwards. Sew shoulder seams of the back and of the front. Serge seams and press towards back part.
6. Serge center edge of the back. Sew center seam from zipper marker up to hem. Press the seam apart, pressing the slit for zipper. Sew the zipper in, from top edge up to the notch.
7. Sew details of lining. Fold lining with neckline right sides together, inserting the lace into the seam. Turn the lining off, leaving 5 mm to closure edges and fix to top edge of the dress. Turn seam allowances along zipper onto right side of the dress and pin to neckline edge on top of lining. Overstitch the neckline. Slash seam allowances on rounded parts and in corner. Turn detail onto right side and press.
8. Overstitch armhole with lining in two steps, inserting the lace into the seam. Turn center edge of the lining and tack to center seam of the back. Stitch lining to inset connecting seam.
9. Press hem of the dress onto wrong side, serge and undersew with invisible stitches.

## **TECHNICAL DRAWING:**

