

Sewing Pattern — Gathered Top 5460

Recommendations on fabric: jersey or elastic fabric.

You will also need: decorative cord of 2.5-3 m length; piping.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for hem, 1.5 cm for shoulder edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front part – 2 pieces

INSTRUCTIONS:

1. Neaten back middle edge. Sew back middle seam and press it towards back right part.
2. Press the piping along center. Overstitch front/back neckline and front/back armhole edge with it.
3. Neaten hem allowance and press to wrong side. Neaten front middle edge. Sew front middle edge. Press front middle edge apart and topstitch front middle seam allowance along both sides at equal distance from seam. (When stitching front middle seam, hem allowance must be in front middle seam.)
4. Neaten back part lower edge and shoulder edges.
5. Sew shoulder edges and press them apart. Topstitch shoulder seam allowance along both sides at equal distance.
6. Neaten side seams and press them backwards.
7. Fold the hem under and topstitch it.
8. Pull the cord into front middle seam allowance and tie. Pull the cord into shoulder seam allowance and tie.

TECHNICAL DRAWING:

