

Sewing Pattern — $\frac{3}{4}$ Trousers 5458

Recommendations on fabric: elastic denim.

You will also need: fusing; 1 zipper; 2 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Right front facing – 2 pieces
2. Left front facing – 2 pieces
3. Back facing – 2 pieces
4. Upper front part – 2 pieces
5. Lower front part – 2 pieces
6. Side front part – 2 pieces
7. Back part – 2 pieces
8. Belt loops – 1 piece
9. Button catch – 1 piece

Fusing: back facing, right/left front facings and button catch.

INSTRUCTIONS:

1. Apply the fusing to wrong side of back facing, right/left front facings and button catch.
2. Sew front part details. Neaten and press joining seam. Make decorative stitch at 0.5 from relive joining seam on front part.
3. Sew back darts. Sew side edges of front/back facings. Press joining seam apart.
4. Neaten side edge of back/front parts, inside leg edges of front/back parts, front edge and middle edge of trousers. Sew side edges of front part and back part together. Press side seams apart.
5. Sew inside leg seams and press them apart. Sew front edge to back edge up to closure notch. Make another stitch along inside leg seam close to front/middle seam.
6. Press closure one-piece facings to wrong side. Sew the zipper under closure left allowance along the

edge. Sew zipper free braid on right one-piece facing. Fold button catch along the center and overstretch lower short edge. Topstitch closure one-piece facing on button catch on trousers left part. Topstitch slit right edge catching facing.

7. Lay facing details right sides together and overstretch upper edge. Topstitch overstretching on lower facing at 0.2 cm from overstretching, stopping at 3 cm before end. Fold yokes to wrong side and press them.

8. Fold the loop belt along the center and overstretch at 0.5-0.7 cm from edges. Turn the detail right side out, placing seam at fold or make edging of 0.1-0.2 cm width into wrong side, and press.

9. Neaten upper edge of lower facings. Cut belt loops of proper size and mark place to sew them. Sew belt loops to facings lower edges. Sew facings to garment upper edge coinciding side seams.

Overstretch facing corners. Slash allowances in corners, turn them right side out and press them.

Topstitch facing neaten edge along joining seam.

10. Neaten hem allowance and press it to wrong side. Topstitch the hem. Make buttonholes into right facing, sew buttons on left one.

Our advice: if you wish, you can, in according with technical sketch, topstitch leg half-belt with clasp on side seam. Do this before stitching inside leg seams.

TECHNICAL DRAWING:

