

Sewing Pattern — Skirt 5456

Recommendations on fabric: denim.

You will also need: fusing, zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Pocket – 2 pieces
2. Flap – 4 pieces
3. Back panel – 1 piece
4. Front panel – 1 piece
5. Front yoke – 2 pieces
6. Back yoke – 2 pieces
7. Belt loop – 1 piece

Fusing: front/back yokes.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front/back yokes.
2. Neaten side edges of front/back panels. Sew right side seam and press it apart. Neaten the hem. Press hem allowance to wrong side.

3. Make and press pleats into front/back panels. Topstitch pleats at 1 from upper edge.
4. Neaten left side edge of outer yokes. Sew right side seam of inner/outer yokes. Neaten lower edge of inner yokes.
5. Lay flaps right sides together and overstitch. Slash allowance of flap rounded corners and turn right side out. Make decorative stitch along outer contour of flaps at 0.5 cm from edge. Neaten flap upper edge.
6. Neaten pocket outer contour and press it according to pattern. Topstitch upper edge on the pocket and mark pocket place on front part. Topstitch the pocket along the contour at 0.2 cm from pocket edge. Topstitch the flap along marking. Fold the flap to right side and topstitch at 0.5 cm from seam.
7. Sew outer yokes to the garment coinciding side seams. Lay yokes right sides together and overstitch yoke upper edges. Topstitch oversteitching on lower yoke at 0.2 cm from oversteitching seam. Fold yokes to wrong side and press ready upper edge of yoke.
8. Sew left side seam up to closure notch. Press closure slits and sew the zipper in caching yokes side edges. Topstitch lower yoke along seam joining upper yokes. Topstitch the hem.
9. Fold belt loops along the center, right sides together, coinciding edges, and overstitch it at 0.5-0.7 cm from edges. Turn right side out placing the seam at fold or make edging of 0.1-0.2 cm width to wrong side, and press it. Cut belt loops and topstitch according to marks.

TECHNICAL DRAWING:

