

Sewing Pattern — Trousers with Cord 5451

Recommendations on fabric: wool.

You will also need: fusing, zipper, hook, eye.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Button catch – 1 piece
2. Front part – 2 pieces
3. Back part – 2 pieces
4. Waistband – 1 piece

INSTRUCTIONS:

1. Apply the fusing to wrong side of waistband and button catch.
2. Sew front/back darts. Press front darts into front center. Press back darts into back center.
3. Neaten: edges of back side part and front part, side leg edges of front part and back part; front edge and middle edge. Sew side seams of front/back parts. Press seams apart.
4. Sew side leg seam and press it apart. Sew front edge and middle edge to closure notch. Make another stitch on side leg seam, close to seam of joining front and middle seam.
5. Press closure one-piece facings into wrong side. Sew the zipper under closure slit allowance (left edge). Sew zipper free braid to right one-piece facing. Fold button catch along the center and overstitch lower short edge. Topstitch closure one-piece facing on button catch at left edge. Topstitch slit right edge catching facing.
6. Make buttonholes into waistband. Press the waistband along the center, wrong side inside, and neaten lower inner edge of waistband.
7. Turn ends of cords under. Fold cords along the center and make stitch at 0.7 cm from bending. Turn cords right side out and press them. Sew ends.
8. Sew the waistband to garment upper edge. Neaten waistband ends, slash allowances in corners,

then turn tight side out. Topstitch waistband lower ready edge on joining seam, then press ready waistband. Pull the cord into waistband.

9. Press the hem under and topstitch.

10. Sew hook on waistband right ends, sew the loop on left one.

TECHNICAL DRAWING:

