

Sewing Pattern — Pleated Skirt 5448

Recommendations on fabric: natural fabric.

You will also need: fusing, zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 6 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Belt loop – 1 piece
2. Back panel – 1 piece
3. Front panel – 1 piece
4. Back yoke – 2 pieces
5. Front yoke – 2 pieces

Fusing: front yoke, back yoke.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front yoke and back yoke.
2. Make pleats into front panel and back panel stitching pleats to notch.
3. Sew front yoke to front panel. Press joining seam towards the yoke.
4. Sew back yoke to back panel. Press joining seam into yoke.
5. Neaten side edges. Sew side seam of front/back panels, leaving a slit for zipper in left side seam. Press side seams apart and press closure slits. Sew the zipper in.
6. Sew side right seam reinforced with fusing front yoke and back yoke. Press joining seam apart. Neaten yoke outer edge.
7. Fold yokes with garment upper edge, right sides together, and overstretch. Topstitch overstretch seam on strengthened yokes at 0.2 cm from overstretching. Turn yokes into wrong side and press garment upper ready edge. Sew turned under side edges of front and back yokes to zipper braids. Topstitch yoke neaten edge to joining seam.

8. Fold belt loop along the center right side inside, coincide edges and overstitch at 0.5-0.7 cm from edges. Turn the loop right side out, place the seam at bending of make edging of 0.1-0.2 cm width into wrong side, then press. Cut belt loops and topstitch them on yokes.
9. Neaten front/back panels hem, press it under and sew by hand.

TECHNICAL DRAWING:

