

# **Sewing Pattern — Top 5443**

Recommendations on fabric: sheer natural fabric.

If the pattern has a double line around it, the seam allowances are included. **Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING**:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

#### Fabric:

- 1. Back cut 1
- 2. Left front cut 1
- 3. Right front cut 1
- 4. Long waistband cut 1
- 5. Short waistband cut 1

## **INSTRUCTIONS**:

- 1. Sew front/back darts. Press darts.
- 2. Sew shoulder seams, serge and press toward back.
- 3. Serge front/back neck edges and sleeve edges. Turn under and topstitch at 0.5 cm from edge.
- 4. Serge side seams separately, then sew seams, leaving an opening on left side seam at mark; press side seams apart. Serge the bottom edge of garment. Then turn under and topstitch.
- 5. Fold the waistband along the center and sew one short side and long side. Turn waistband right



side out and press. Topstitch at 0.1 cm from waistband edge. Sew the waistband to left front. Serge joining seam and topstitch it.

6. Serge side edge of short waistband. Apply the waistband to right front and sew the three edges. Turn the waistband right side out and press. Topstitch at 0.1 cm from waistband edge.

\*You can trim waistband end with buckle.

## **TECHNICAL DRAWING:**

