

## Sewing Pattern — Dress 4217

Recommendations on fabric: two-side fabrics suitable for dresses; lace.

You will also need: blind zipper; fusing.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on hem of the dress – 3.0 cm; hem of sleeve and along front part neckline vertical edged - 1.5 cm; along vertical and lower cuts of fall edge - 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back part - 2 details
2. Right side front part - 1 detail
3. Central front part - 1 detail
4. Left side front part - 1 detail
5. Front part inner yoke — 1 detail
6. Back neckline facing – 2 details

Lace:

1. Front part yoke - 1 detail
2. Sleeve — 2 details

Fusing: back part neckline facing

### **INSTRUCTIONS:**

1. Apply fusing to details.
2. Sew waist and shoulder darts on back part. Press depths towards center.
3. Apply fusing to vent on both details of back part from wrong side. Serge middle edges separately on each detail. Mark middle seam line (vent foldline) from right side. Sew middle edge of back part from zipper marker up to vent corner. Slash vent corner seam allowance. Press seam allowances of middle seam apart, pressing slit for zipper, press vent onto left side. Press right side of the vent

- on 1 cm onto wrong side and topstitch. Topstitch seam allowances of the vent with machine stitch. Sew in zipper.
4. Sew central front part with side parts. Press seam allowances towards center and serge.
  5. Sew darts on yoke and inner yoke of front part. Press depths towards center. Slash upper edge of inner yoke near markers. Serge upper edge from armholes up to markers, press onto right(!) side and topstitch. Fold inner yoke with outer right sides together and overstretch horizontal section of neckline. Slash seam allowances in corners. Turn inner yoke onto wrong side, press, fix to outer on armholes edges and lower edge and sew further as one detail. Serge vertical edges of front part neckline, press seam onto wrong side and topstitch.
  6. Serge vertical and lower cuts of fall edge with thin rolled seam. Put fall edge onto front part, make plaits according to markers and fix on top and side edges.
  7. Stitch yoke to front part, press seam allowances upwards and serge.
  8. Sew side seams, press seam onto back part and serge.
  9. Serge outer edge of the back part neckline facing. Fold dress with facing right sides together, leveling neckline edges. Turn the facing away leaving 5 mm to zipper edges and pin to top edge of the dress. Turn seam allowances on right side of the dress along zipper and pin to neckline edge over facing. Overstretch neckline edge, starting and finishing the stitch exactly near marked line of shoulder seam. Slash seam allowances on rounded parts, turn details out and press. Tack facing to zipper tape.
  10. Sew shoulder seams, inserting front part between back part and back part facing. Press seam allowances, serge. Turn the facing onto wrong side.
  11. Sew edge of sleeve, press and serge seam allowances. Sew sleeve into armhole, leveling notches. Press and serge seam allowances. Serge lower edge of sleeve, press seam onto wrong side and topstitch.
  12. Serge hem seam allowance of the dress, press onto wrong side and undersew with invisible stitches.

### **TECHNICAL DRAWING:**

