

Sewing Pattern — Silk Trousers 5435

Recommendations on fabric: silk, jersey.

You will also need: jersey coupons for waistband and cuffs, elastic braid of 3 cm length.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Waistband
4. Cuffs – 2 pieces

INSTRUCTIONS:

1. Sew side edges and neaten them. Press side seams backwards.
2. Sew inside leg seam and neaten it. Press inside leg seams backwards.
3. Sew front edge and middle edge. Neaten front seam and middle sea. Make another seam along the crotch aloes to joining seam of front seam and middle seam.
4. Sew cuffs side edges in a ring, then neaten them. Sew cuffs to garment lower edges, gathering hems and stretching cuffs. Neaten joining seam.
5. Cut elastic braid according to your girths. Sew side edges of elastic braid. Sew waistband side edges, then neaten them. Sew elastic braid to lower edge of jersey waistband.
6. Coincide waistband side edges and garment side seams, gathering garment upper edge and stretching waistband lower edge. Remove tacking. Sew elastic braid to the waistband. Neaten joining seam.

TECHNICAL DRAWING:

