

Sewing Pattern — Skirt 5434

Recommendations on fabric: lightweight wool, viscose, suitable skirt fabric

You will also need: zipper, eyelets, decorative cord and fusible interfacing

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Front panel – cut 1
2. Front facing– cut 1
3. Front flounce 1 – cut 1
4. Front flounce 2 – cut 1
5. Lower front panel– cut 1
6. Back panel – cut 1
7. Back flounce 1 – cut 1
8. Back facing – cut 1
9. Lower back panel – cut 1
10. Back flounce 2 – cut 1

Interfacing: front/back facing

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the front and back facings.
2. Serge the front/back panel side edges; stitch the side seams leaving an opening in the left seam for zipper; press the seams open.
3. Serge the lower panel side edges. Serge the side edges of the flounces. Sew the side seams; press the seams open.
4. With side seams matching, stitch the skirt lower panel to the skirt, sandwiching the flounce 1 between them; serge the seam; press the seam allowances upwards.
5. Stitch the flounce 2 to the skirt lower panel; serge the seam; press the seam allowances upwards.
6. Sew the right edge of front and the back facings together; press seam open. Serge the facing lower raw edge. Sew in the zipper. Sew the facing to the top edge of skirt. Understitch, turn onto wrong side and topstitch. Turn side seam allowance of facing under, and slip-stitch to zipper tape. Fasten lower edge of facing to inside along connecting seams.
7. Serge the flounces' lower edges; press onto wrong side, and topstitch.
9. Install eyelets according to marks; thread cord through the eyelets.

TECHNICAL DRAWING:

