

Sewing Pattern — Wrap Skirt 5431

Recommendations on fabric: denim.

You will also need: zip and iron-on interfacing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 for all seams, 0 cm for the hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back panel – 2 pieces
2. Right front panel – 1 piece
3. Left front panel – 1 piece
3. Front facing – 2 pieces
4. Back facing – 2 pieces

Interfacing: front/back facing.

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the front facing and the back facing.
2. Stitch the front/back darts; press the darts towards the front/back centre.
3. Make pleats at the right front panel.
4. Neaten the back centre edges; stitch the back centre seam leaving a zipper opening.
5. Neaten and stitch the garment side edges; press the seams open.
6. Join the front and back facing across the side seams.
Press the seams open. Neaten the facing lower edge.
7. Insert the zip. Overstitch the skirt waistline with the facing. Topstitch the seam allowances to the facing 0,2 cm in.
8. Overlap the left front panel with the right front panel; topstitch the right panel edge. Fix the front panels together through the waistline seam with 2 cm seam.
9. You can finish the skirt hem by applying a fringe.

TECHNICAL DRAWING:

