

Sewing Pattern — Skirt 5430

Recommendations on fabric: wool or half-wool fabric.

You will also need: zip and fusing

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3 cm for the skirt hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Fly facing – 1 piece
2. Zip guard – 1 piece
3. Carrier – 1 piece
4. Back panel – 1 piece
5. Front panel – 2 pieces
6. Upper side front – 2 pieces
7. Pocket facing - 2 pieces
8. Pocket – 2 pieces
9. Front waistband – 4 pieces
10. Back waistband – 2 pieces

Fusing: front/back under waistband.

INSTRUCTIONS:

1. Apply fusing to the wrong side of the front/back under waistband piece.
2. Stitch the back darts; press the darts to the back centre.
3. With right sides inside, press the carrier piece in half lengthways; stitch 0,5-0,7 cm from the fold; turn right side out and press. Cut carriers according to the pattern.

4. Stitch the pocket piece to the upper side front piece; neaten the seam; press the seam allowances downwards and topstitch to the pocket. With right sides together, overstretch the pocket entrance with the pocket facing; topstitch the pocket opening 1 cm below the fold. Stitch the side front piece to the pocket facing around the inner edges. Neaten this seam. Stitch the pocket to the front at the side/waist edges.
5. Stitch the front/back top waistband side edges; press the seams open. Stitch the waistband to the skirt waist edge, placing the carriers between them.
6. Stitch the fly facing to the right front. Neaten the front and the facing centre edges. Stitch the front centre seam up to the zipper notches.
7. Neaten the skirt side edges; stitch the side seams; press the seams open.
8. Stitch the zip tape to the slit left edge and to the right fly facing. Press the fly facing to the wrong side of the garment. Tack the fly facing to the garment. Fold the zip guard inside out and overstretch along a short edges; turn it right side out; neaten the zip guard side edges together. Place the zip guard under the left edge of the zip and tack. Topstitch on the on the right side of the garment through the garment, zip tape and the zip guard.
9. Cut the waistband right front end according to the front centre edge plus 1 cm for the seam allowance. Stitch the under waistband side edges; press the seams open. Neaten the under waistband inner edge. With right sides together and the under waistband uppermost, stitch along the upper edge. Topstitch the seam allowances to the under waistband. Fold the waistband front ends under; topstitch the waistband right end and the zipper opening right edge from the waistband upper edge to the end of the zip through the fly facing according to the design. Topstitch the waistband left end. Topstitch the carrier upper edges to the waistband.
10. Neaten the garment hem; press the hem under and topstitch.

TECHNICAL DRAWING:

