

Sewing Pattern — Skirt 5419

Recommendations on fabric: silk or viscose fabric

You will also need: zip, lace braid and fusing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Left back panel – 1 piece
2. Right back panel – 1 piece
3. Front panel – 1 piece
4. Front facing – 1 piece
5. Back facing – 2 pieces
6. Flounce – 1 piece
7. Small flounce – 1 piece

Fusing: front/back facing.

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the front facing and the back facing.
2. Stitch the front/back darts; press them towards the front/back centre.
3. Neaten the back centre edges; stitch the back centre seam up to the zipper notches. Press the seam open.
4. Neaten the front and the back lower edges. Topstitch the lace braid upper edge to the front and the back lower fashion seamline.

5. Neaten the skirt side edges; stitch the side seams; press the seams open.
6. Neaten the flounce upper and side edges; put the flounces under the lace braid and topstitch them to the garment.
7. Stitch the front and the back facing together; press the seams open. Neaten the facing lower edge.
8. Insert the zip. With the facing uppermost, stitch the facing to the skirt waist edge. Topstitch the seam allowances to the facing 0,2 cm from the seam. Fold the facing centre edges under and slipstitch them to the zip tape.
9. Neaten the flounce lower edges; press the seam allowances under and topstitch.

TECHNICAL DRAWING:

