

## Sewing Pattern —Top with Lace Inset 5417

Recommendations on fabric: lightweight fabric with elastan, lace

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



#### **CUTTING**:

#### Fabric:

- 1. Central back 2 pieces
- 2. Side back 2 pieces
- 2. Cup 2 pieces
- 3. Front inset 1 piece
- 4. Central front 2 pieces
- 5. Middle front 2 pieces
- 6. Side front 2 pieces
- 7. Back tie 2 pieces
- 8. Front tie 2 pieces

### **INSTRUCTIONS:**

- 1. Stitch and neaten the front central seam; press the seam.
- 2. Stitch the front curved edges; neaten the seams; press the seams.
- 3. Neaten the cup front edge; press the seam allowances under. Gather the cup lower edge; stitch the cup to the front piece; neaten the seam; press the seam allowances downwards.
- 4. Stitch the back pieces together. Neaten the seams; press the seam allowances to the side pieces.
- 5. Stitch the back central edges; neaten the seam; press the seam allowances to the right piece.
- 6. Stitch the garment side edges; neaten the seams and press them backwards.
- 7. Neaten the back upper edge and the armhole edges. Press the seam allowances under and topstitch 0.5 cm from the fold.
- [8. Fold the tie piece in half lengthways and stitch 1 cm from the foldline, stitch the tie one end. Turn the tie right side out; press and stitch to the garment.
- 9. Neaten the garment hem; press the hem under and topstitch.



10. Cut the lace decorative inset. Fold the inset top edge under and topstitch with zigzag. Topstitch the inset to the caps with zigzag also.

# TECHNICAL DRAWING:

