

Sewing Pattern —Skirt with Flounces 5416

Recommendations on fabric: silk or viscose fabric

You will also need: zip and iron-on interfacing

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back panel – 2 pieces
2. Front panel – 1 piece
3. Front facing – 1 piece
4. Back facing – 2 pieces
5. Flounce – 4 pieces

Interfacing: front/back facing

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the front facing and the back facing.
2. Stitch the front/back darts; press them towards the front/back centre.
3. Neaten and stitch the skirt side edges; press the seams open.
4. Stitch the front and the back facing together; press the seams open. Neaten the facing lower raw edge.
5. Stitch the flounce side edges, leaving the flounce centre seam unstitched. Neaten the seams; press them.
6. Stitch the flounce to the skirt lower edge; neaten the seam; press the seam allowances upwards.
7. Neaten the skirt/flounce centre edges. Stitch the back centre seam, leaving a zipper opening. Insert the zip.
8. With the facing uppermost, stitch the facing to the skirt waist edge. Topstitch the seam allowances to the facing 0,2 cm from the seam. Fold the facing centre edges under and slipstitch them to the zip tape.
9. Stretching the fabric, neaten the flounce lower edge.

TECHNICAL DRAWING:

