

Sewing Pattern — Skirt 5361

Recommendations on fabric: denim.

You will also need: fusing; eyelets, and zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front shaped yoke – 4 pieces
2. Front yoke centre inset – 2 pieces
3. Front panel – 2 pieces
4. Back panel – 2 pieces
5. Back yoke – 4 pieces

Fusing: shaped yoke, front yoke centre inset; inner back/front yokes

INSTRUCTIONS:

1. Apply the fusing to the wrong side of the shaped yoke, front yoke centre inset; inner back/front yokes.
2. Stitch the back darts. Press the darts backwards.
3. Stitch the front panel centre edges; neaten the seam. Then press the seam to the right centre front and make decorative stitch 0.2 cm away from the joining seam.
4. Stitch and neaten the side seams. Press them backwards.

5. Stitch shaped front/back yoke side edges; press the seams open. Neaten the inner yoke front/back lower edges.
6. With right sides together, stitch the facing pieces along the upper edge leaving the back centre edges free. Trim the seam allowances on the rounded corners trim and notch the seam allowances on the shaped yoke. Turn the yoke right side out. Press it.
7. With right sides together, stitch the yoke inset pieces along the upper edge. Press the seam. Topstitch the edging 0.2 cm below. Neaten the front inset lower/side edges.
8. Stitch the yoke to the garment; neaten the back yoke centre edges and the back panel centre edges. Stitch the back centre edges up to the closure notch. Press the seam open. Sew the zipper in. Topstitch the yoke neaten edge.
9. Topstitch the front yoke inset to the garment.
10. Attach eyelets. Pull in and tie the cord. Fold under and topstitch the hem.

TECHNICAL DRAWING:

