

Sewing Pattern — Corset 5360

Recommendations on fabric: denim

You will also need: fusing, cotton lining, 6 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Centre back – 2 pieces
2. Side back – 2 pieces
3. Side front – 2 pieces
4. Right centre front – 2 pieces
5. Left centre front – 2 pieces
6. Pocket facing – 2 pieces
7. Pocket – 2 pieces

Lining:

1. Centre back – 2 pieces
2. Side back – 2 pieces
3. Side front – 2 pieces

Fusing: inner centre front, pocket facing.

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the inner left/right centre front, pocket facing.

2. Stitch the front curved edges; press the seams open.
3. Press the pocket facing and stitch it to the pocket top edge. Neaten the pocket edges and press them to the wrong side according to the pattern. Topstitch the pocket to the front piece.
4. Stitch the back centre seam. Stitch the back curved edges. Press the seams open.
5. Stitch the side seams and press them open.
6. Stitch the shoulder seams and press them open.
7. With right sides together, stitch the inner center front to the outer pieces along the front edges and around the neck stop the stitching 5 cm before the shoulder edges.
8. Stitch the underlining leaving the shoulder edges unstitched. Press the underlining.
9. Stitch the underlining to the garment.
10. Press under and overstitch the garment hem with underlining leaving 10 cm slit unstitched. Turn the garment through this slit. Sew the slit edges together.
11. Make buttonholes in the right centre front and sew buttons to the left piece.

TECHNICAL DRAWING:

