

Sewing Pattern — Corset 5359

Recommendations on fabric: denim.

You will also need: iron-on interfacing, cotton lining, 6 buttons, cord and 22 eyelets.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. centre back – 2 pieces
2. side front – 2 pieces
3. centre front – 4 pieces
4. side front – 2 pieces

Lining:

1. centre back – 2 pieces
2. side back – 2 pieces
3. side front – 2 pieces

Fusing:

centre front inner pieces.



INSTRUCTIONS:

1. apply the interfacing to the wrong side of the centre front inner pieces.
2. stitch the front/back curved edges; press the seams open.
3. stitch the side seams; press them open.
4. stitch the shoulder seams; press them open.
5. with right sides together, stitch the inner center front to the outer pieces along the front edges and around the neck stop the stitching 5 cm before the shoulder edges.
6. stitch the underlining. press the seams.
7. with right sides together, pin the lining to the garment; stitch the underlining to the center front inner edges. stitch the lining and centre front shoulder edges. overstretch the back neckline and raw part of the front neckline with the underlining. overstretch the armhole edge upper parts with the underlining leaving 10 cm slits in the lower parts. cut the seam allowances close to the seams. pull the front pieces right side out through the shoulder slits and turn the garment right side out through one of open side seams. overstretch the armhole lower parts.
8. press the garment hem to the wrong side and blindstitch it. stitch the center front to the hem seam allowance.
9. make buttonholes in the right front; sew buttons on the left one.
10. attach the eyelets to the back center and pull the cord through.

TECHNICAL DRAWING:

