

## Sewing Pattern — Dress 4212

Recommendations on fabric: thin costume fabric of natural or mixed fibers.

You will also need: fusing; zipper; 2 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1 cm, hem – 1,5 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Side front part - 2 details
4. Central front part – 1 detail
5. Collar - 4 details
6. Facing of the armhole of back part - 2 details
7. Facing of the armhole of front part - 2 details

Fusing:

1. Collar - 2 details
2. Facing of the armhole of back part - 2 details
3. Facing of the armhole of front part - 2 details

### **INSTRUCTIONS:**

1. Apply fusing to corresponding details .
2. Sew middle edge of back part from top up to vent. Press seam allowances and vent onto left side and serge. Topstitch seam allowances of the vent on top edge with machine stitch. Sew relieve seams on back part, press seam allowances towards center and serge.

3. Sew middle edges of collars pairwise, press seam allowances apart. Fold collars right sides together and overstitch on outer contour. Slash seam allowances on rounded parts, turn collar onto right side, serge, press. Stitch collar to side parts of front part.
4. Serge upper edge of central front part and press it onto wrong side on marked line. Stitch central front part to side part, serge seam allowances of relieve seam and press to side edge.
5. Sew shoulder seams, slashing front part in corner. Press seam allowances towards back part and serge. Sew collar in the back part neckline, press seam allowances and serge.
6. Serge separately left side edges. Sew left side seam from the armhole up to marker and from marker downwards. Press the seam apart, pressing slit for zipper. Sew in zipper. Sew right side seam, press seam onto back part and serge.
7. Sew side and shoulder edges of the facings of the armhole, serge outer edges. Fold facings with armholes right sides together and overstitch. Slash seam allowances onto rounded parts. Turn facings onto wrong side, press. Fix facings to side and shoulder seams.
8. Serge hem of the garment, press onto wrong side and undersew with invisible stitches.
9. Serge buttonholes on lower parts of collar, sew buttons on central front part accordingly.

**TECHNICAL DRAWING:**

